



adjustable
economical
self leveling
re-usable



power generation



gas / oil transmission



pump systems

RotaChock for all rotating machines



P/N	rated load [kN]	OD Ø [mm]	ID Ø [mm]	minimum height [mm]	design height [mm]	maximum height [mm]	standard boltsize M	reduced minimum height [mm]	optional boltsize M	pitch [mm]	weight [kg]
RC2	100	51	17	30	34	38	10/16	23	18	1.6	0,4
RC3	150	76	20	35	42	48	16/18	23	24	1.6	1,1
RC4	200	102	28	40	47	53	20/24	28	30	2.1	2,2
RC4.5	300	114	31	45	53	60	20/27	31	33	2.1	3,1
RC5	400	127	36	50	60	69	28/33	32	39	2.1	4,3
RC6	600	152	41	55	65	74	33/39	37	45	2.1	6,8
RC7	900	178	46	60	68	76	39/45	45	48	3.2	10,1
RC8	1200	203	54	70	81	91	48/52	50	56	3.2	15,3
RC9	1600	229	66	75	84	93	56/60	58	68	3.2	20,7
RC10	2000	254	74	80	89	98	64/68	63	76	4.2	27,3

Configuration options:

tall line
tall top parts

Materials:

carbon steel
alloy steel
316L stainless

RotaChock ACE, Anti- Corrosion Enhanced

The ACE is a rugged solution for rust problems. We have implemented a new material process to our RotaChock products.

Simply the Best!

- Adjustment range
- Minimize installation time
- Simple re-adjustment
- Cost effective
- No soft foot

